

Pb Free Plating Product

## SFF1601G thru SFF1608G



16.0 Amperes Insulated Common Cathode Super Fast Recovery Rectifiers

**Features**


- ★ Super fast switching for high efficiency
- ★ Low forward voltage drop
- ★ High current capability
- ★ Low reverse leakage current
- ★ High surge current capability

**Application**

- ★ Automotive Inverters and Solar Inverters
- ★ Plating Power Supply, SMPS and UPS
- ★ Car Audio Amplifiers and Sound Device Systems

**Mechanical Data**

- ★ Case: ITO-220AB full plastic isolated package
- ★ Epoxy: UL 94V-0 rate flame retardant
- ★ Terminals: Solderable per MIL-STD-202 method 208
- ★ Polarity: As marked on diode body
- ★ Mounting position: Any
- ★ Weight: 1.75 gram approximately



| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted)   |                    |           |           |           |           |              |           |           |           |      |
|--|--------------------|-----------|-----------|-----------|-----------|--------------|-----------|-----------|-----------|------|
| PARAMETER  | SYMBOL             | SFF 1601G | SFF 1602G | SFF 1603G | SFF 1604G | SFF 1605G    | SFF 1606G | SFF 1607G | SFF 1608G | UNIT |
| Maximum repetitive peak reverse voltage  | V <sub>RRM</sub>   | 50        | 100       | 150       | 200       | 300          | 400       | 500       | 600       | V    |
| Maximum RMS voltage  | V <sub>RMS</sub>   | 35        | 70        | 105       | 140       | 210          | 280       | 350       | 420       | V    |
| Maximum DC blocking voltage  | V <sub>DC</sub>    | 50        | 100       | 150       | 200       | 300          | 400       | 500       | 600       | V    |
| Maximum average forward rectified current  | I <sub>F(AV)</sub> | 16        |           |           |           |              |           |           |           | A    |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load            | I <sub>FSM</sub>   | 125       |           |           |           |              |           |           |           | A    |
| Maximum instantaneous forward voltage (Note 1)<br>I <sub>F</sub> = 8 A                         | V <sub>F</sub>     | 0.975     |           |           |           | 1.3          |           | 1.7       |           | V    |
| Maximum reverse current @ Rated V <sub>R</sub> T <sub>J</sub> =25 °C<br>T <sub>J</sub> =125 °C | I <sub>R</sub>     |           |           |           |           | 10           |           | 400       |           | μA   |
| Maximum reverse recovery time (Note 2)   | T <sub>rr</sub>    |           |           |           |           | 35           |           |           |           | ns   |
| Typical junction capacitance (Note 3)  | C <sub>j</sub>     | 80        |           |           |           |              |           | 50        |           | pF   |
| Typical thermal resistance   | R <sub>θJC</sub>   |           |           |           |           | 3.0          |           |           |           | °C/W |
| Operating junction temperature range   | T <sub>J</sub>     |           |           |           |           | - 55 to +150 |           |           |           | °C   |
| Storage temperature range  | T <sub>STG</sub>   |           |           |           |           | - 55 to +150 |           |           |           | °C   |

Note 1: Pulse Test with PW=300μs, 1% Duty Cycle

Note 2: Reverse Recovery Test Conditions: I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>RR</sub>=0.25A.

Note 3: Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL REVERSE CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4 TYPICAL FORWARD CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE




FIG.6- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM

